



FEATURES

- High speed & quality weighing indicator
- RFI/EMI screened
- PC interface
- Single pass automatic span calibration
- WATCH-DOG circuitry
- Fueling stations, Liquid or gaseous
- Weight back-up ● Easy operation
- Print date & time by inner clock
- Standard RS-232C interface (Serial printer)
Platform scale
- Applications : Platform scale

OPTION

- RS-422/485 interface



SPECIFICATIONS

Model	EXP - 2000A	EXP - 5500
Input Sensitivity	1 μ V/D	
Load cell Excitation Voltage	DC 5V, 300mA	DC 10V, 300mA (Up to 8 Load cell)
Zero Adjust Range	- 10mV ~ 10mV	
System Linearity	0.01% F.S.	
A/D Internal Resolution	1/130,000	1/200,000
A/D External Resolution	1/10,000 (Max.)	
A/D Conversion Rate	10 times/sec	20 times/sec
Span Calibration	Full Digital Calibration (Single pass automatic span calibration)	
Display	LED 6 digit	VFD 7 digit
Operating Temperature	-10 °C ~ +40 °C	
Power Source	AC 110/220V, 50/60Hz	
Power Consumption	2W	10W
Dimension (W × D × H)	180 × 228 × 157 mm	324 × 148 × 218 mm
Product Weight	7.4kg	12.3kg
Classification Code	Ex d IIB T4	