POS System

User Friendly Optimal POS System

XANDER7 is all-in-one type POS system designed for popular POS terminal model. Top I/O interface for easy interface and PCAP Multi touch screen for detailed touch sensitivity adapted. XANDER7 is best choice for entry level POS system environment.

Flat Touch type popular POS system

- Refined & easy installation design
- Convenient Top I/O interface
- Dual Sided Smart Card(IC Card) Reader
- Adapted PCAP Multi Touch Screen
- Easy maintenance

Power		Specification
CPU	Intel J1900	Intel® Celeron® J1900 (2.0 Ghz) Quad-Core Processor / Fanless
Main	Memory	2GB Standard DDR3L 1600 MT/s, Socket 1 x SODIMM (up to 8GB)
	Storage	M.2 SSD64 (Option : 2.5" SATA-|| 320GB HDD & SSD(64GB/128GB)
Primary Display	LCD	15" TFT LED Backlight
	Resolution	1024 x 768
	Touch Projective	Capacitive Touch 10Point
	Speaker	1 x 1W
	USB	6 (Rear4, Back 2, USB 2.0 x 6), 4 internal (Reserved for MSR, SCR, i-Button/Touch Controller)
	Serial	6 (COM1~3 RJ-45, Full Signal with 5V/12V Power Output set BIOS), (COM4~6 internal Full Signal, 5V/12V Power Output set Jumper) Reserved for IC_MSR/Cash Drawer Port)
	LAN	1 x Gigabit Ethernet, RJ-45
	VGA	1 x VGA (With Power Output)
	Audio	1 x Line-out
	DC-IN	1 x (4 Pin Connector) 12V OUT(2nd Display Power)
User Environment	Temperature	Operating -25°C to 65°C, Storage -35°C to 75°C
Size	Dimension	414 x 251 x 361 mm (W x D x H)
	Weight	8.4kg
	MSR	ISO || Track Reading
Optional Peripherals	OS	Windows 7, 10, POSReady7, Windows 10 LoT Entry
	2nd Display	9.7" TFT LCD(1024 x 768)
		20x2 Line VFD